

## WRECKER

# 25CS

Make heads turn with the 25CS and put it to work while meeting 25-ton contract requirements with ease.

With the 25CS, you benefit from the power and versatility of the larger Composite Sliders packaged in a smaller, more agile unit. A robust frame translates into a durable and reliable equipment that offers you the payload you need for most recoveries, without sacrificing on fun.

An economic and resistant partner who will be there for you every day, whether for a simple tow, or an accident scene.



### WRECKER SPECIFICATIONS

- 25-Ton Rated lifting capacity
- Working hydraulic pressure 3000 PSI
- 73" Sliding recovery boom
- Composite body 100' wide (including fenders)

### BOOM SPECIFICATIONS

- 2-stage recovery boom
- Boom structural rating fully retracted: 50,000 lbs
- Boom structural rating fully extended: 20,000 lbs
- Reach past tailgate: 167"
- Maximum Boom working height: 272"
- Range of elevation: 0° - 55°
- 360° sheave head

### MINIMUM FRAME REQUIREMENTS

- Front Axle: Minimum 12,000 lbs capacity
- Rear Axle: Minimum 21,000 lbs capacity
- Minimum frame RBM: 2,750,000 in.lbs per rail
- Minimum CLA 140" (from cab to center of rearmost axle)



CAPACITY

25 TONS



STANDARD  
WINCHES

25,000 LBS



BOOM REACH

167"

**NETC**

NETRUCKCENTER.COM

Sales: (603) 658-7171

Service: (603) 778-8158