

## WRECKER

# CSR50

The new CSR50 and its Sliding Rotator technology will take you to a whole new level of performance. The new retractable easy access control panel propels while you also benefit from 25% more storage space, additional rear compartment and access door for stabilizer pads.

The entire product structure has been redesigned to offer more rigidity and better resistance to torsion. Quick release underlift hydraulic connections, allowing effortless hydraulic connection even with residual pressure in the system, also completes the new CSR. The CSR50 is a versatile recovery truck that can tow its fair share.



### WRECKER SPECIFICATIONS

- 50-ton hydraulic sliding-rotating wrecker boom
- Average body weight : 37,000 lbs
- 40-ton safe lifting capacity (with 25% safety factor)
- 101,5" wide heavy duty body

### BOOM SPECIFICATIONS

- V-shaped 3-stage telescopic boom
- Boom structural rating fully retracted: 100,000 lbs
- Boom structural rating fully extended: 20,000 lbs
- Reach past tailgate: 299"
- Maximum Boom working height: 440"
- Range of elevation: 0° - 65°
- 360° sheave head
- D-rings on each boom sections

### MINIMUM FRAME REQUIREMENTS

- Front Axle: Minimum 18,000 lbs capacity
- Rear Axle: Minimum 46,000 lbs capacity
- Minimum frame RBM: 4,500,000 in.lbs
- Minimum CLA 198"  
(from cab to center of rearmost axle)



50 TONS



40,000 LBS



299"

