

DETACHABLE UNIT

QUICKSWAP

Efficient in every sense of the word, the Quicksnap saves big on fuel and maintenance costs while maximizing the possibilities... and your profits.

Quicksnap's tough components and lightweight design make it a true workhorse. Add a winch to your Quicksnap and use it as a supporting recovery unit.

Take advantage of the detachable design to push your limits during high seasons, and adapt during slower periods.



QUICKSWAP SPECIFICATIONS

- Towing capacity: 80,000 lbs
- Underlift lifting capacity: 35,000 lbs
- Basic weight: 6000 lbs
- Dual cylinders for underlift elevation

STANDARD EQUIPMENT

- 3-stage HD Underlift
- Hydraulic underlift extension
- Hydraulic tilt boom
- Hydraulic fold
- Removable front stands
- Manual controls
- Safety chain pockets
- Aluminum fenders
- Fork storage and holders
- Tie-down chains

MINIMUM FRAME REQUIREMENTS

- Front Axle: Minimum 12,000 lbs capacity
- Rear Axle: Minimum 40,000 lbs capacity
- Minimum frame RBM: 3,250,000 in.lbs per rail
- Minimum wheelbase: 250" HD Underlift
- Minimum wheelbase: 275" SHD Underlift



35,000 LBS+



80,000 LBS



6,000 LBS



NETRUCKCENTER.COM

Sales: (603) 658-7171

Service: (603) 778-8158