

WRECKER

20CS

The 20CS is light, agile and strong ; the perfect recruit to conquer new markets. The Slider System offers unmatched payload, while the smaller size of th 20CS means incredible maneuverability and versatility.

Surprisingly easy to handle, the 20CS shines in the harshest urban conditions. This work-beast is built small enough for narrow roads, yet strong enough to never let you down. Maximum performance, astonishing versatility and reduced maintenance costs, all combined into a stylish composite body. We've built your newest business partner.



WRECKER SPECIFICATIONS

- 20-Ton Rated lifting capacity
- Working hydraulic pressure 3000 PSI
- Dual 20,000 lbs planetary winches
- Composite body 100" wide (including fenders)

BOOM SPECIFICATIONS

- 2-stage, 73" Sliding recovery boom
- Boom structural rating fully retracted: 40,000 lbs
- Boom structural rating fully extended: 15,000 lbs
- Reach past tailgate: 147"
- Maximum Boom working height: 256"
- Range of elevation: 0° - 55°
- 360° sheave head

MINIMUM FRAME REQUIREMENTS

- Front Axle: Minimum 10,000 lbs capacity
- Rear Axle: Minimum 20,000 lbs capacity
- Minimum frame RBM: 2,150,000 in.lbs per rail
- Minimum CLA 140"
(from cab to center of rearmost axle)



CAPACITY

20 TONS



STANDARD
WINCHES

20,000 LBS



BOOM REACH

147"



NETRUCKCENTER.COM

Sales: (603) 658-7171

Service: (603) 778-8158