

CARRIER

10TB

Large volume of calls for light duty vehicles? With the 10TB, rest assured you are backed by a compact unit built to deliver the same toughness and durability as our heavier duty models.

The 10TB's oversized components and various deck options can be catered to suit your needs. Consider our strong and light aluminum deck that significantly increase your payload

Whether it be for long haul, or working in the city, you'll look forward to powering through it all with the 10TB.



CARRIER SPECIFICATIONS

- Tow bar lift rating: 5,000 lbs @ 0" / 1,800 lbs @ 48"
- Operating pressure: 2600 psi
- Tow rating : 9,000 lbs
- Deck width : 102"

STANDARD EQUIPMENT

- Standard winch: 8,000 lbs
- Dual controls - lever type
- Pressure gauge
- Independent hydraulic tow bar
- Wheel lift system
- Fixed headboard with chain rack (winch embedded in chain rack)
- 3 marker lights & 3 chain slots per side
- Hydraulic oil tank with filter - 12 GAL
- Hydraulic gear pump, direct mount - 17 GPM

MINIMUM FRAME REQUIREMENTS

- Cab to axle: 120" - 160"
- Minimum frame resisting bending moment: 900,000 lbs*in / rail

NRC SAFE LOADER™ AUTOMATIC WHEEL-LIFT SYSTEM

- NRC SAFE LOADER™, also known as a self loader, extends, adjusts and lifts the car or truck into place. Our system consists of a low mounted rear view camera and flexible in-cab control that make it possible to perform a tow job without leaving the comfort of your driver's seat. Note that it's also possible to operate the clamping mechanism using the manual levers located at each side's control panel.
- Fully extended 10TB: 1800 lbs



DECK RATING

10,000 LBS



AVAILABLE BED LENGTH

18' - 21,5'



STANDARD WINCH

8,000 LBS

